

# Optimus 32 Kiosk



Freestanding



Wall Mount



Integrated 2D Barcode Scanner\*



Integrated Thermal Printer\*



Integrated EFTPOS Solution  
(mounting holes only)

\* Optional configuration

**SEVOR**



Freestanding

Wall Mount

## SPECIFICATIONS

SIZE / RESOLUTION	31.5" TFT LCD / 1080 x 1920 pixels
BRIGHTNESS	300 cd/m <sup>2</sup>
CONTRAST RATIO	3000:1
TOUCH SCREEN PANEL	Projected capacitive touch (10 point)

## ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT - Freestanding	840 (W) x 2050 (H) x 500 (D) mm   100 kg
- Wall Mount	680 (W) x 1325 (H) x 165 (D) mm   55 kg
CHASSIS MATERIAL	Metal sheet
TEMPERATURE	Operating: 0°C to 35°C   Storage: -20°C to 60°C
HUMIDITY	Operating: 20% to 80%   Storage: 10% to 90%
POWER CONSUMPTION	AC input: 100 V to 240 V   180 W (max.)

## MODEL OPTIONS

BASE	Freestanding base
MOTION DETECTOR	Microwave sensor, range: 3 cm to 500 cm
CAMERA	2-megapixel CMOS camera
2D BARCODE READER	640 x 480 CMOS image reader, mobile screen friendly
PRINTER	3" paper width, 250mm/sec fast printing, auto cutter
MSR	3-track magnetic stripe card reader

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

**QLOGIK Technologies, Inc. | 3630 Peachtree Rd NE | Atlanta, GA 30326 USA**  
**Phone +1 (678) 974 2807 | Mobile +1 (678) 793 3481**  
**Web: [www.qlogik.us](http://www.qlogik.us) Sales: [info@qlogik.us](mailto:info@qlogik.us)**

Quality – Safety – Versatility