

iSPOS 10



Wall Mount Capable



IP66 Whole Unit*



VESA Mount Capable

* Desktop type only

SEÑOR

iSPOS S106/i106

Vast Potential in Limited Space

The iSPOS S106/i106 brings to you Senor's unparalleled quality and durability standard in a **compact-sized all-in-one** solution.

Its 10.4" high brightness, high resolution LED screen with multi-touch support offers the user comfort and ease on a fully functional surface. Powered by Intel® Quad Core Celeron / Dual Core i3 platform and fitted with SSD storage, the iSPOS S106/i106 exhibits **superior performance and reliability** to manage high volume transactions effectively.



A wide array of **integrated options** for seamless and wireless communication ensures the system is well connected.

The iSPOS S106/i106 can be implemented for a diverse range of applications in the **retail, hospitality, banking and industrial** sectors.

iSPOS S106/i106 WS

Sleek Wall Mount Panel PC

The wall mount solution, iSPOS/i106 S106 WS (IP54 rating) is ideally suited for sites with restricted space that require multiple access points for self-service activities.

Ideal application for

- Kitchen bump screen
- Guests check-In
- Membership registration
- Information operator
- Warehouse management
- Government facilities



Key Features

Nano Coating & Rubber Seals
Hydrophobic & grease-repelling

Fanless & Ventless
Easy maintenance

Aluminium Die-cast Casing
Robust & durable

IP66 Rating#
Water & dust resistance

Mounting Options
Wall / VESA mount

Internal Power Supply
Secured protection

LED Backlight
Bezel-less Design

IP66 available on desktop type.



iSPOS S106/i106 WP Desktop Self Service Kiosk

The iSPOS S106/i106 WP (IP43 rating) is a compact sized, fully integrated desktop kiosk with an integrated thermal printer. It optimises an innovative modular construction design to simplify the maintenance process.

Ideal application for

- Self-service transactions
- Registration point
- Queue docket generation
- Ticket collection point



2-line VFD
(custom order)



8.4" LCD Customer Display
(custom order)



High Speed Thermal Printer
250mm/s



SPECIFICATIONS

PROCESSOR

iSPOS S106

Intel Quad Core Celeron J1900 2.0 GHz

iSPOS i106

Intel Dual Core i3-6100U 2.3 GHz

SYSTEM MEMORY

4 GB DDR3L RAM (up to 8 GB)

4 GB DDR4 RAM (up to 32 GB)

STORAGE DEVICE

Half-slim SATA SSD

Half-slim SATA SSD

DISPLAY

SIZE / RESOLUTION

10.4" LED / 1024 x 768 pixels

BRIGHTNESS

400 cd/m²

TOUCH SCREEN PANEL

Projected capacitive touch

I/O INTERFACE

USB PORT

4 x USB 2.0

SERIAL PORT

2 x DB9

VIDEO PORT

1 x VGA

AUDIO

2 x built-in speakers

ETHERNET PORT

1 x Gigabit LAN 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS

POSReady 7 / 7 Pro / 10 IoT / 10 Pro

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT

Desktop: 276 (W) x 230 (H) x 165 (D) mm | 3.0 kg
 Wall Mount: 276 (W) x 223 (H) x 42 (D) mm | 3.0 kg
 WP: 276 (W) x 405 (H) x 405 (D) mm | 5.3 kg (with TP80 printer)

CHASSIS MATERIAL

Heat-dissipating solid aluminium die-cast casing with nano-coating technology

VESA PATTERN

75 x 75 mm / 100 x 100 mm

IP RATING

Desktop: IP66 | Wall Mount: IP54 | WP: IP43

TEMPERATURE

Operating: 0°C to 40°C | Storage: -20°C to 60°C

HUMIDITY

Operating: 0% to 80% | Storage: 10% to 90% (non-condensing)

POWER CONSUMPTION

12 V / 3.5 A, internal power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER

3-track MSR, RFID (125 kHz/13.56 MHz)

WIRELESS LAN

Wi-Fi 802.11 b/g/n

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

QLOGIK Technologies, Inc. | 3630 Peachtree Rd NE | Atlanta, GA 30326 USA
Phone +1 (678) 974 2807 | Mobile +1 (678) 793 3481
Web: www.qlogik.us Sales: info@qlogik.us

Quality – Safety – Versatility

QLOGIK