

iSPOS WWP



Floor Stand with Signage Board *



Integrated Thermal Printer



Internal Power Supply

* Optional

SENIOR



SPECIFICATIONS

	iSPOS 900	iSPOS i75
PROCESSOR	Intel Quad Core Celeron J1900 2.0 GHz (Turbo Boost up to 2.42 GHz)	Intel Dual Core i7-6500U 2.5 GHz (Turbo Boost up to 3.1 GHz)
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE DEVICE	2.5" removable SATA HDD/SSD	2.5" removable SATA HDD/SSD

DISPLAY

SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels 17" TFT LCD / 1280 x 1024 pixels
BRIGHTNESS	350 cd/m ²
TOUCH SCREEN PANEL	15": resistive touch / projected capacitive touch 17": resistive touch

I/O INTERFACE

USB PORT	Front: 1 x USB 2.0CBack: 3 x USB 2.0 (up to 4 x USB 2.0)
SERIAL PORT	2 x DB9 (up to 4 x RJ50)
VIDEO PORT	1 x VGA
AUDIO PORT	2 x built-in speakers / 1 x 3.5 mm mic in/line out
CASH DRAWER PORT	1 x RJ12 (24 V)
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	POSReady 7 / 7 Pro / 10 IoT / 10 Pro
----------------	--------------------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	15" iSPOS WP: 390 (W) x 470 (H) x 260 (D) mm 15 kg 17" iSPOS WP: 446 (W) x 520 (H) x 260 (D) mm 17 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing
VESA PATTERN	75 x 75 mm / 100 x 100 mm
IP RATING	IP66 whole unit
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)
POWER CONSUMPTION	12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR, RFID (supports MIFARE, 13.56 MHz/125 kHz), Smart card reader, Fingerprint reader
CUSTOMER DISPLAY	2-line VFD / 8.4"/10"/15" TFT LCD
WIRELESS LAN	Integrated 802.11 b/g/n

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

QLOGIK Technologies, Inc. | 3630 Peachtree Rd NE | Atlanta, GA 30326 USA
Phone +1 (678) 974 2807 | Mobile +1 (678) 793 3481
Web: www.qlogik.us Sales: info@qlogik.us

Quality - Safety - Versatility

QLOGIK